



### Properties

<b>Design</b>	Complete pistons
<b>Operating pressure</b>	up to 10 bar
<b>Sliding speed max.</b>	1,0 m/s
<b>Temp. min.</b>	-30 °C
<b>Temp. max.</b>	110 °C
<b>Media</b>	Mineral oils Water-air
<b>Installation</b>	push onto piston recess with the rubber side and affix with washer and nut.
<b>Material</b>	NBR 85° Shore A, with steel core
<b>Application</b>	Pneumatics



Toleranz / Tolerance		
D	d	E
H11	f8	± 0,50



### Note

Tolerance: D= H11; d= f8; E= +/-0.5

### Description

Complete pistons.

### Ordering information

For special operating conditions (fluid, temperature, pressure ...) please contact us.

Alternative material possible: FPM, EPDM.

Item					
Identification	D (mm)	d (mm)	P (mm)	E (mm)	e (mm)
TDOP 25	25	8	15,6	12	3,8
TDOP 32	32	8	20,0	15	3,8
TDOP 40	40	10	27,0	18	4,8
TDOP 50	50	10	37,0	18	4,8
TDOP 60	60	12	43,0	22	6,0
TDOP 63	63	12	43,0	22	6,0
TDOP 063-1	63	16	43,0	22	6,0
TDOP 65	65	12	43,0	25	6,0
TDOP 70	70	12	50,0	25	6,0
TDOP 80	80	16	55,0	24	6,0
TDOP 100	100	20	75,0	26	7,0
TDOP 125	125	20	95,0	26	9,6
TDOP 160	160	27	129,0	30	10,8
TDOP 200	200	27	169,0	35	11,4