
# HK CB L
Overcentre valve CB

## Properties

**Operating pressure** max. 350 bar






## Note

These valves must be set according to the application.

## Description

load-holding function to 210bar (with setting 280 bar, opening of load pressure 0 bar)
Load-dependent opening for controlling negative (dragging) loads
back pressure on connection 2 can impair the functioning of the valve
closing pressure >= 85% of the opening pressure
Note! Relief function by screwing in the spindle

## Item

| Identification | Pressure setting range min. | Pressure setting range max. | Qmax | A | B | Screw-in housing | Screw-in thread | AF | Tightening torque | Level control ratio | Weight |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | (bar) | (bar) | (L/min) | (mm) | (mm) | | | (mm) | (N-m) | | (kg) |
| **HK CB BY LHN** | 70 | 280 | 20 | 50,0 | 35,0 | HK EBAM / HK EBAT / HK EBY / HK EBYS / HK YEU | T-11A | 22 | 50,0 | 1:2 | 0,5 |
| **HK CB CA LIN** | 25 | 105 | 60 | 50,0 | 35,0 | HK EBAM / HK EBAT / HK EBY / HK EBYS / HK YEU | T-11A | 22 | 50,0 | 1:3 | 0,5 |
| **HK CB CA LHN** | 70 | 280 | 60 | 50,0 | 35,0 | HK EBAM / HK EBAT / HK EBY / HK EBYS / HK YEU | T-11A | 22 | 50,0 | 1:3 | 0,5 |
| **HK CB EA LIN** | 25 | 105 | 120 | 61,0 | 35,0 | HK BCV / HK BCVS / HK BCW / HK BCWS / HK YAV | T-2A | 28 | 65,0 | 1:3 | 0,5 |
| **HK CB EA LHN** | 70 | 280 | 120 | 61,0 | 35,0 | HK BCV / HK BCVS / HK BCW / HK BCWS / HK YAV | T-2A | 28 | 65,0 | 1:3 | 0,5 |

## Accessories

| | |
|---|---|
| **HK GEH BC** | Valve housing for cartridge valve T-2A |
| **HK GEH EBA** | Housing sandwich plate with measurement connctn. for cart. valve T-11A |
| **HK GEH EBY** | Housing sandwich plate with measurement connctn. for cart. valve T-11A |
| **HK GEH YA** | Valve housing for cartridge valve T-2A |
| **HK GEH YE** | Valve housing for cartridge valve T-11A |
| **HK HR SUN** | Hand wheel for cartridge valve SUN |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*