


# CHEM EPDM

Chemical supply hose

## Properties

<b>Application</b>	chemical industries Sea and industrial waste water
<b>Special features</b>	suitable for use as pressure hose in the chemical industry
<b>Standard</b>	DIN EN 12115
<b>Inner layer</b>	chemical resistant, black, smooth EPDM rubber
<b>Insert</b>	two highly resistant textile inserts and two antistatic copper braids
<b>Outer layer</b>	abrasion resistant, flame-retardant, ozone and weather resistant CR rubber
<b>Colour</b>	black
<b>Temp. range</b>	min. flexible to -35°C max. depending on the medium 95°C Temperature peaks up to 120°C



## Item

Identification	Inches	Internal Ø (mm)	External Ø (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)	Roll length (m)
CHEM 19-6 EPDM	3/4"	19,0	31	16,0	64	125	40
CHEM 25-6 EPDM	1"	25,4	37	16,0	64	150	40
CHEM 32-6 EPDM	1.1/4"	32,0	44	16,0	64	175	40
CHEM 38-6.5 EPDM	1.1/2"	38,0	51	16,0	64	225	40
CHEM 51-8 EPDM	2"	50,8	67	16,0	64	275	40
CHEM 63-8 EPDM	2.1/2"	63,5	79	16,0	64	300	40
CHEM 76-8 EPDM	3"	76,2	92	16,0	64	350	40
CHEM 102-8 EPDM	4"	101,6	118	16,0	64	450	40