

AGRI WAS LR

Flat water hose

HANSA FLEX

Properties

Application	Agricultural technology Industry and construction
Special features	extremely durable due to inserts with high tear strength
Inner layer	PVC
Insert	Textile insert
Outer layer	NBR with longitudinal protective ribs
Colour	black
Temp. min.	-20 °C
Temp. max.	100 °C
Media	Water Air Oil petrol



Note

Also suitable for air, oil, petrol

Item

Identification	Inches	Internal Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Roll length (m)
AGRI WAS 19 LR	3/4"	19	1,5	25,0	100
AGRI WAS 25 LR	1"	25	1,5	25,0	100
AGRI WAS 32 LR	1.1/4"	32	1,5	20,0	100
AGRI WAS 38 LR	1.1/2"	38	1,5	16,0	100
AGRI WAS 52 LR	2"	52	2,0	16,0	100
AGRI WAS 65 LR	2.1/2"	65	2,0	16,0	100
AGRI WAS 76 LR	3"	75	2,5	16,0	100
AGRI WAS 90 LR	3.1/2"	90	2,5	16,0	100
AGRI WAS 102 LR	4"	102	2,5	16,0	100
AGRI WAS 127 LR	5"	127	3,0	16,0	100
AGRI WAS 152 LR	6"	152	3,0	16,0	100

BD = Working pressure