

# AGRI WAS LR

Flat water hose

**HANSA FLEX**

## Properties

<b>Application</b>	Agricultural technology Industry and construction
<b>Special features</b>	extremely durable due to inserts with high tear strength
<b>Inner layer</b>	PVC
<b>Insert</b>	Textile insert
<b>Outer layer</b>	NBR with longitudinal protective ribs
<b>Colour</b>	black
<b>Temp. min.</b>	-20 °C
<b>Temp. max.</b>	100 °C
<b>Media</b>	Water Air Oil petrol



## Note

Also suitable for air, oil, petrol

## Item

Identification	Inches	Internal Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Roll length (m)
AGRI WAS 19 LR	3/4"	19	1,5	25,0	100
AGRI WAS 25 LR	1"	25	1,5	25,0	100
AGRI WAS 32 LR	1.1/4"	32	1,5	20,0	100
AGRI WAS 38 LR	1.1/2"	38	1,5	16,0	100
AGRI WAS 52 LR	2"	52	2,0	16,0	100
AGRI WAS 65 LR	2.1/2"	65	2,0	16,0	100
AGRI WAS 76 LR	3"	75	2,5	16,0	100
AGRI WAS 90 LR	3.1/2"	90	2,5	16,0	100
AGRI WAS 102 LR	4"	102	2,5	16,0	100
AGRI WAS 127 LR	5"	127	3,0	16,0	100
AGRI WAS 152 LR	6"	152	3,0	16,0	100

BD = Working pressure