AGRI WAS LR

Flat water hose



Properties				
Application	Agricultural technology Industry and construction			
Special features	extremely durable due to inserts with high tear strength			
Inner layer	PVC			
Insert	Textile insert			
Outer layer	NBR with longitudinal protective ribs			
Colour	black			
Temp. min.	-20 °C			
Temp. max.	100 °C			
Media	Water Air Oil petrol			



Note

Also suitable for air, oil, petrol

Item						
Identification	Inches	Internal Ø	Wall thickness	Operating pressure	Roll length	
AGRI WAS 19 LR	3/4"	19	1,5	25,0	100	
AGRI WAS 25 LR	1"	25	1,5	25,0	100	
AGRI WAS 32 LR	1.1/4"	32	1,5	20,0	100	
AGRI WAS 38 LR	1.1/2"	38	1,5	16,0	100	
AGRI WAS 52 LR	2"	52	2,0	16,0	100	
AGRI WAS 65 LR	2.1/2"	65	2,0	16,0	100	
AGRI WAS 76 LR	3"	75	2,5	16,0	100	
AGRI WAS 90 LR	3.1/2"	90	2,5	16,0	100	
AGRI WAS 102 LR	4"	102	2,5	16,0	100	
AGRI WAS 127 LR	5"	127	3,0	16,0	100	
AGRI WAS 152 LR	6"	152	3,0	16,0	100	

BD = Working pressure