

### Properties

Application	Agricultural technology Industry and construction
Special features	extremely durable due to inserts with high tear strength
Inner layer	PVC
Insert	Textile insert
Outer layer	NBR with longitudinal protective ribs
Colour	black
Temp. min.	-20 °C
Temp. max.	100 °C
Media	Water Air Oil petrol



### Note

Also suitable for air, oil, petrol

### Item

Identification	Inches	Internal Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Roll length (m)
<b>AGRI WAS 19 LR</b>	3/4"	19	1,5	25,0	100
<b>AGRI WAS 25 LR</b>	1"	25	1,5	25,0	100
<b>AGRI WAS 32 LR</b>	1.1/4"	32	1,5	20,0	100
<b>AGRI WAS 38 LR</b>	1.1/2"	38	1,5	16,0	100
<b>AGRI WAS 52 LR</b>	2"	52	2,0	16,0	100
<b>AGRI WAS 65 LR</b>	2.1/2"	65	2,0	16,0	100
<b>AGRI WAS 76 LR</b>	3"	75	2,5	16,0	100
<b>AGRI WAS 90 LR</b>	3.1/2"	90	2,5	16,0	100
<b>AGRI WAS 102 LR</b>	4"	102	2,5	16,0	100
<b>AGRI WAS 127 LR</b>	5"	127	3,0	16,0	100
<b>AGRI WAS 152 LR</b>	6"	152	3,0	16,0	100

BD = Working pressure