# BKR BH HB RD

Plug valve for hammer drill

## Properties

| | |
|---|---|
| **Application** | for compressed air supply in construction, compressors, hose lines and hammers. |
| **Connection 1** | BSP external thread, cylindrical |
| **Connection 2** | round external thread |
| **Standard** | DIN 20030 |
| **Scope of supply** | with brass plug and malleable cast iron lever |
| **Temp. min.** | -15 °C |
| **Temp. max.** | 80 °C |
| **Media** | Compressed air |
| **Material** | Malleable cast iron |
| **Surface** | electro galvanised |



## Note

Input thread with counter nut SW 32/41

Hammer drill valves DIN 20030 without lever without lever stop, without bleeding.

## Description

Self-sealing; under pressure, the conical plug is pressed against the housing and seals valve off. This prevents sealing wear.

## Item

| Identification | DN* | G1 | G2 | h (mm) | l (mm) | AF (mm) | Operating pressure |
|---|---|---|---|---|---|---|---|
| **BKR BH NW 20 HB 32 RD** | 12 | G 3/4" -14 | Rd 32 x 1/8" | 95 | 140 | 32 | PN 10 |
| **BKR BH NW 25 HB 32 RD** | 16 | G 1" -11 | Rd 32 x 1/8" | 95 | 120 | 36 | PN 10 |

DN = Nominal diameter, nominal width – G1 + G2 = Threads of connections 1+2 – AF = Width across flats

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*