BKR BH HB RD

Plug valve for hammer drill

Properties

Application	for compressed air supply in construction, compressors, hose lines and hammers.
Connection 1	BSP external thread, cylindrical
Connection 2	round external thread
Standard	DIN 20030
Scope of supply	with brass plug and malleable cast iron lever
Temp. min.	-15 °C
Temp. max.	80 °C
Media	Compressed air
Material	Malleable cast iron
Surface	electro galvanised



Note

Input thread with counter nut SW 32/41

Hammer drill valves DIN 20030 without lever without lever stop, without bleeding.

Description

Self-sealing; under pressure, the conical plug is pressed against the housing and seals valve off. This prevents sealing wear.

Item

Identification	DN*	G1	G2	h (mm)	l (mm)	AF (mm)	Operating pressure
BKR BH NW 20 HB 32 RD	12	G 3/4" -14	Rd 32 x 1/8"	95	140	32	PN 10
BKR BH NW 25 HB 32 RD	16	G 1" -11	Rd 32 x 1/8"	95	120	36	PN 10

DN = Nominal diameter, nominal width – G1 + G2 = Threads of connections 1+2 – AF = Width across flats

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.