

EURO WAS BL

Flat water hose

HANSA FLEX

Properties

Application	Agricultural technology Construction industry Mining Shipbuilding
Special features	maximum tensile and cohesive strength no expansion under pressure flat rollable with no interconnections
Inner layer	PVC
Insert	one polyester braided insert
Outer layer	PVC
Colour	blue
Temp. min.	-10 °C
Temp. max.	60 °C
Media	Water



Item

Identification	Inches	Internal Ø (mm)	BD* at 20°C (bar)	Burst pressure (bar)	Roll length (m)
EURO WAS 1 BL	1"	25	8,5	25,5	100
EURO WAS 1 1/4 BL	1.1/4"	32	8,5	25,5	100
EURO WAS 1 1/2 BL	1.1/2"	38	8,5	25,5	100
EURO WAS 2 BL	2"	51	6,5	19,5	100
EURO WAS 2 1/2 BL	2.1/2"	63	6,5	19,5	100
EURO WAS 3 BL	3"	76	5,5	16,5	100
EURO WAS 4 BL	4"	102	5,5	16,5	100
EURO WAS 5 BL	5"	127	3,0	9,0	100
EURO WAS 6 BL	6"	152	3,0	9,0	100
EURO WAS 8 BL	8"	204	2,5	7,0	100

BD = Working pressure