

KT MM

Conical nozzle

Properties

Application	in construction, mining and tunnel building
Connection 1	Sealing cone
Sealing form 1	Outer cone
Connection 2	Hose connection
Standard	DIN 8537 / 20 033
Temp. min.	-40 °C
Temp. max.	95 °C
Media	Compressed air, water
Material	Steel
Surface	electro galvanised



Note

The conical nozzles are without a safety collar
 KT19MM-PH for hydraulic pressing with press sleeve.
 Conical nozzles 1:3 cone generally with additional O-ring seal.

Item

Identification	for hose ID (mm)	Length (mm)	b (mm)	Cone	Operating pressure
KT 10 MM	10	78	28	1:3	PN 25
KT 10 MM-2	10	70	24	1:4	PN 25
KT 13 MM	13	80	28	1:3	PN 25
KT 13 MM-2	13	79	24	1:4	PN 25
KT 15 MM	15	80	28	1:3	PN 25
KT 15 MM-2	15	79	24	1:4	PN 25
KT 19 MM	19	80	28	1:3	PN 25
KT 19 MM-2	19	80	24	1:4	PN 25
KT 19 MM-PH	19	80	28	1:3	PN 25
KT 25 MM	25	90	33	1:3	PN 25
KT 25 MM-2	25	85	30	1:3	PN 25
KT 25 MM-3	25	85	29	1:3	PN 25
KT 32 MM	32	120	40	1:3	PN 25
KT 35 MM	35	125	35	1:3	PN 25
KT 38 MM	38	125	48	1:3	PN 25
KT 42 MM	42	130	57	1:3	PN 25
KT 50 MM	50	140	68	1:3	PN 25
KT 53 MM	53	140	68	1:3	PN 25
KT 75 MM	75	189	98	1:3	PN 25

Accessories

UEM KT	Union nut for conical nozzles
UEM KT RD	Union nut for conical nozzles