

# KT MM

## Conical nozzle

### Properties

<b>Application</b>	in construction, mining and tunnel building
<b>Connection 1</b>	Sealing cone
<b>Sealing form 1</b>	Outer cone
<b>Connection 2</b>	Hose connection
<b>Standard</b>	DIN 8537 / 20 033
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	95 °C
<b>Media</b>	Compressed air, water
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Note

The conical nozzles are without a safety collar  
 KT19MM-PH for hydraulic pressing with press sleeve.  
 Conical nozzles 1:3 cone generally with additional O-ring seal.

### Item

Identification	for hose ID (mm)	Length (mm)	b (mm)	Cone	Operating pressure
KT 10 MM	10	78	28	1:3	PN 25
KT 10 MM-2	10	70	24	1:4	PN 25
KT 13 MM	13	80	28	1:3	PN 25
KT 13 MM-2	13	79	24	1:4	PN 25
KT 15 MM	15	80	28	1:3	PN 25
KT 15 MM-2	15	79	24	1:4	PN 25
KT 19 MM	19	80	28	1:3	PN 25
KT 19 MM-2	19	80	24	1:4	PN 25
KT 19 MM-PH	19	80	28	1:3	PN 25
KT 25 MM	25	90	33	1:3	PN 25
KT 25 MM-2	25	85	30	1:3	PN 25
KT 25 MM-3	25	85	29	1:3	PN 25
KT 32 MM	32	120	40	1:3	PN 25
KT 35 MM	35	125	35	1:3	PN 25
KT 38 MM	38	125	48	1:3	PN 25
KT 42 MM	42	130	57	1:3	PN 25
KT 50 MM	50	140	68	1:3	PN 25
KT 53 MM	53	140	68	1:3	PN 25
KT 75 MM	75	189	98	1:3	PN 25

### Accessories

<b>UEM KT</b>	Union nut for conical nozzles
<b>UEM KT RD</b>	Union nut for conical nozzles