KT MM
Conical nozzle

HANSA-FLEX

Properties

Application	in construction, mining and tunnel building
Connection 1	Sealing cone
Sealing form 1	Outer cone
Connection 2	Hose connection
Standard	DIN 8537 / 20 033
Temp. min.	-40 °C
Temp. max.	95 °C
Media	Compressed air, water
Material	Steel
Surface	electro galvanised



Note

The conical nozzles are without a safety collar
KT19MM-PH for hydraulic pressing with press sleeve.
Conical nozzles 1:3 cone generally with additional O-ring seal.

Item

Identification	for hose ID (mm)	Length (mm)	b (mm)	Cone	Operating pressure
KT 10 MM	10	78	28	1:3	PN 25
KT 10 MM-2	10	70	24	1:4	PN 25
KT 13 MM	13	80	28	1:3	PN 25
KT 13 MM-2	13	79	24	1:4	PN 25
KT 15 MM	15	80	28	1:3	PN 25
KT 15 MM-2	15	79	24	1:4	PN 25
KT 19 MM	19	80	28	1:3	PN 25
KT 19 MM-2	19	80	24	1:4	PN 25
KT 19 MM-PH	19	80	28	1:3	PN 25
KT 25 MM	25	90	33	1:3	PN 25
KT 25 MM-2	25	85	30	1:3	PN 25
KT 25 MM-3	25	85	29	1:3	PN 25
KT 32 MM	32	120	40	1:3	PN 25
KT 35 MM	35	125	35	1:3	PN 25
KT 38 MM	38	125	48	1:3	PN 25
KT 42 MM	42	130	57	1:3	PN 25
KT 50 MM	50	140	68	1:3	PN 25
KT 53 MM	53	140	68	1:3	PN 25
KT 75 MM	75	189	98	1:3	PN 25

Accessories

UEM KT	Union nut for conical nozzles
UEM KT RD	Union nut for conical nozzles

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.