

## Properties

<b>Special features</b>	highly flexible and sturdy free from LABS, separating agents and grease low flow resistance
<b>Inner layer</b>	black, porous, smooth EPDM lining
<b>Insert</b>	synthetic threads
<b>Outer layer</b>	EPDM resistant to ozone and UV radiation
<b>Colour</b>	black
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	95 °C
<b>Temp. range</b>	Temperature peaks up to 110°C
<b>Media</b>	Water



## Note

Working pressure is relative to room temperature

## Item

Identification	Inches	Internal Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Min. bending radius (mm)	Roll length (m)
<b>WAS 10-3.5 STRAHL</b>	3/8"	10	3,5	20,0	60	50
<b>WAS 13-3 STRAHL</b>	1/2"	13	3,0	20,0	80	40
<b>WAS 16-3.5 STRAHL</b>	5/8"	16	3,5	20,0	100	40
<b>WAS 19-4 STRAHL</b>	3/4"	19	4,0	20,0	120	40
<b>WAS 25-4.5 STRAHL</b>	1"	25	4,5	20,0	150	40
<b>WAS 32-6 STRAHL</b>	1.1/4"	32	6,0	20,0	200	50