

# UEM KT RD

Union nut for conical nozzles

## Properties

**Application** in construction, mining and tunnel building

**Connection 1** Rund nut thread

**Standard** DIN 8537 / 20 033

**Temp. min.** -40 °C

**Temp. max.** 95 °C

**Media** Compressed air, water

**Material** Malleable cast iron

**Surface** electro galvanised



## Item

Identification	G1	Length (mm)	b (mm)	Hole Ø (mm)	Operating pressure
UEM RD 32	Rd 32 x 1/8"	28	65	23,0	PN 25
UEM RD 32-2	Rd 32 x 1/8"	28	65	27,5	PN 25
UEM RD 38	Rd 38 x 1/8"	33	76	29,0	PN 25
UEM RD 46	Rd 46 x 1/6"	36	86	35,0	PN 25
UEM RD 55	Rd 55 x 1/6"	38	95	42,0	PN 25
UEM RD 62	Rd 62 x 1/6"	44	105	49,0	PN 25
UEM RD 75	Rd 75 x 1/6"	50	137	61,0	PN 25
UEM RD 105	Rd 105 x 1/4"	60	158	-	PN 25

G1 = Thread of connection 1

## Accessory for following products

KT MM Conical nozzle

## Spare part for following products

KT UEM RD Conical nozzle with union nut