UEM KT RD

Union nut for conical nozzles

Properties

Application	in construction, mining and tunnel building
Connection 1	Rund nut thread
Standard	DIN 8537 / 20 033
Temp. min.	-40 °C
Temp. max.	95 °C
Media	Compressed air, water
Material	Malleable cast iron
Surface	electro galvanised



Item

Identification	G1	Length (mm)	b (mm)	Hole Ø (mm)	Operating pressure
UEM RD 32	Rd 32 x 1/8"	28	65	23,0	PN 25
UEM RD 32-2	Rd 32 x 1/8"	28	65	27,5	PN 25
UEM RD 38	Rd 38 x 1/8"	33	76	29,0	PN 25
UEM RD 46	Rd 46 x 1/6"	36	86	35,0	PN 25
UEM RD 55	Rd 55 x 1/6"	38	95	42,0	PN 25
UEM RD 62	Rd 62 x 1/6"	44	105	49,0	PN 25
UEM RD 75	Rd 75 x 1/6"	50	137	61,0	PN 25
UEM RD 105	Rd 105 x 1/4"	60	158	-	PN 25

G1 = Thread of connection 1

Accessory for following products

KT MM	Conical nozzle

Spare part for following products

KT UEM RD	Conical nozzle with union nut

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.