

### Properties

<b>Application</b>	for mortar, concrete, screed supply on pumps, sprayers and plastering machines
<b>Connection 1</b>	BSP external thread, cylindrical
<b>Connection 2</b>	Coupling female connection
<b>Special features</b>	TÜV tested
<b>Media</b>	Mortar, concrete, screed
<b>Material</b>	Steel Malleable cast iron
<b>Surface</b>	electro galvanised



### Note

Type size 25 has one lever, all other type sizes have 2 levers.

Note: Parts must only be replaced with parts of the same type sizes!

### Item

Identification	G1	Type size	Ident dimension	Max. working pressure (bar)	System
<b>MM AG 10/25</b>	G 1" -11	25	35,5	50	22 / 23,5
<b>MM AG 10-X25</b>	G 1" -11	X25	42,0	50	22 / 23,5
<b>MM AG 54/35</b>	G 1.1/4" -11	35	51,0	50	22
<b>MM AG 15/42</b>	G 1.1/2" -11	42	54,0	50	22 / 23,5
<b>MM AG 20/50</b>	G 2" -11	50	64,0	50	22
<b>MM AG 25/50</b>	G 2.1/2" -11	50	64,0	50	22

### Spare parts

<b>MDR</b>	Seal for mortar coupling
------------	--------------------------