

Properties

| | |
|-------------------------|--|
| Application | for mortar, concrete, screed supply on pumps, sprayers and plastering machines |
| Connection 1 | BSP external thread, cylindrical |
| Connection 2 | Coupling female connection |
| Special features | TÜV tested |
| Media | Mortar, concrete, screed |
| Material | Steel Malleable cast iron |
| Surface | electro galvanised |



Note

Type size 25 has one lever, all other type sizes have 2 levers.

Note: Parts must only be replaced with parts of the same type sizes!

Item

| Identification | G1 | Type size | Ident dimension | Max. working pressure (bar) | System |
|---------------------|--------------|-----------|-----------------|-----------------------------|-----------|
| MM AG 10/25 | G 1" -11 | 25 | 35,5 | 50 | 22 / 23,5 |
| MM AG 10-X25 | G 1" -11 | X25 | 42,0 | 50 | 22 / 23,5 |
| MM AG 54/35 | G 1.1/4" -11 | 35 | 51,0 | 50 | 22 |
| MM AG 15/42 | G 1.1/2" -11 | 42 | 54,0 | 50 | 22 / 23,5 |
| MM AG 20/50 | G 2" -11 | 50 | 64,0 | 50 | 22 |
| MM AG 25/50 | G 2.1/2" -11 | 50 | 64,0 | 50 | 22 |

Spare parts

MDR Seal for mortar coupling