

**Properties**

<b>Application</b>	for mortar, concrete, screed supply on pumps, sprayers and plastering machines
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Connection 2</b>	Coupling female connection
<b>Special features</b>	TÜV tested
<b>Media</b>	Mortar, concrete, screed
<b>Material</b>	Steel Malleable cast iron
<b>Surface</b>	electro galvanised

**Note**

Type size 25 and MMIG10-MA have one lever, all other type sizes have 2 levers.

Note: Parts must only replaced with parts of the same type sizes!

**Item**

Identification	G1	Type size	Ident dimension	Max. working pressure (bar)	System
<b>MM IG 10/25</b>	G 1" -11	25	35,5	50	22 / 23,5
<b>MM IG 10-MA</b>	G 1" -11	-	38,0	50	May
<b>MM IG 10-X25</b>	G 1" -11	X25	42,0	50	22 / 23,5
<b>MM IG 10/35</b>	G 1" -11	35	51,0	50	22
<b>MM IG 54/35</b>	G 1.1/4" -11	35	51,0	50	22
<b>MM IG 15/35</b>	G 1.1/2" -11	35	51,0	50	22
<b>MM IG 15/42</b>	G 1.1/2" -11	42	54,0	50	22 / 23,5
<b>MM IG 20/50</b>	G 2" -11	50	64,0	50	22
<b>MM IG 25/65</b>	G 2.1/2" -11	65	74,0	25	22 / 23,5

**Spare parts**

**MDR** Seal for mortar coupling