

MM IG

Mortar coupling, female part IGR

Properties

Application	for mortar, concrete, screed supply on pumps, sprayers and plastering machines
Connection 1	BSP cylindrical internal threads
Connection 2	Coupling female connection
Special features	TÜV tested
Media	Mortar, concrete, screed
Material	Steel Malleable cast iron
Surface	electro galvanised



Note

Type size 25 and MMIG10-MA have one lever, all other type sizes have 2 levers.

Note: Parts must only be replaced with parts of the same type sizes!

Item					
Identification	G1	Type size	Ident dimension	Max. working pressure (bar)	System
MM IG 10/25	G 1" -11	25	35,5	50	22 / 23,5
MM IG 10-MA	G 1" -11	-	38,0	50	May
MM IG 10-X25	G 1" -11	X25	42,0	50	22 / 23,5
MM IG 10/35	G 1" -11	35	51,0	50	22
MM IG 54/35	G 1.1/4" -11	35	51,0	50	22
MM IG 15/35	G 1.1/2" -11	35	51,0	50	22
MM IG 15/42	G 1.1/2" -11	42	54,0	50	22 / 23,5
MM IG 20/50	G 2" -11	50	64,0	50	22
MM IG 25/65	G 2.1/2" -11	65	74,0	25	22 / 23,5

Spare parts

MDR Seal for mortar coupling