

# MULTI EPDM

Universal hose

**HANSA FLEX**

## Properties

<b>Application</b>	Agricultural technology Construction industry Systems engineering
<b>Special features</b>	ozone, oil resistant and weatherproof
<b>Inner layer</b>	EPDM
<b>Insert</b>	synthetic threads
<b>Outer layer</b>	Chloroprene rubber
<b>Colour</b>	black
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	120 °C



## Item

Identification	Inches	Internal Ø (mm)	External Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)
<b>MULTI 13-3.2 EPDM</b>	1/2"	13,0	19,4	3,2	30,0	90	130
<b>MULTI 19-4.2 EPDM</b>	3/4"	19,0	27,4	4,2	25,0	75	190
<b>MULTI 25-4.5 EPDM</b>	1"	25,0	34,0	4,5	20,0	60	250
<b>MULTI 32-5.5 EPDM</b>	1.1/4"	32,0	43,0	5,5	12,0	36	320
<b>MULTI 38-6 EPDM</b>	1.1/2"	38,0	50,0	6,0	12,0	36	380
<b>MULTI 51-8.5 EPDM</b>	2"	50,8	68,0	8,6	7,0	70	510