

### Properties

<b>Application</b>	for mortar, concrete, screed supply on pumps, sprayers and plastering machines
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Connection 2</b>	Coupling male connection
<b>Special features</b>	TÜV tested
<b>Media</b>	Mortar, concrete, screed
<b>Material</b>	Steel Malleable cast iron
<b>Surface</b>	electro galvanised



### Note

Type size 25 and MMIG10-MA have one lever, all other type sizes have 2 levers.

Note: Parts must only be replaced with parts of the same type sizes!

### Item

Identification	G1	Type size	Ident dimension	Max. working pressure (bar)	System
<b>MV IG 10/25</b>	G 1" -11	25	35,0	50	22 / 23,5
<b>MV IG 10-MA</b>	G 1" -11	-	37,5	50	May
<b>MV IG 10-X25</b>	G 1" -11	X25	41,0	50	22 / 23,5
<b>MV IG 10/35</b>	G 1" -11	35	49,5	50	22
<b>MV IG 54-X25</b>	G 1.1/4" -11	X25	41,0	50	22 / 23,5
<b>MV IG 54/35</b>	G 1.1/4" -11	35	49,5	50	22
<b>MV IG 54/50</b>	G 1.1/4" -11	50	63,0	50	22
<b>MV IG 15/35</b>	G 1.1/2" -11	35	49,5	50	22
<b>MV IG 15/42</b>	G 1.1/2" -11	42	53,0	50	22 / 23,5
<b>MV IG 15/50</b>	G 1.1/2" -11	50	63,0	50	22
<b>MV IG 20/35</b>	G 2" -11	35	49,5	50	22
<b>MV IG 20/50</b>	G 2" -11	50	63,0	50	22
<b>MV IG 25/50</b>	G 2.1/2" -11	50	63,0	50	22
<b>MV IG 25/65</b>	G 2.1/2" -11	65	73,0	25	22 / 23,5