

Properties

| | |
|-------------------------|--|
| Application | for mortar, concrete, screed supply on pumps, sprayers and plastering machines |
| Connection 1 | BSP cylindrical internal threads |
| Connection 2 | Coupling male connection |
| Special features | TÜV tested |
| Media | Mortar, concrete, screed |
| Material | Steel Malleable cast iron |
| Surface | electro galvanised |



Note

Type size 25 and MMIG10-MA have one lever, all other type sizes have 2 levers.

Note: Parts must only be replaced with parts of the same type sizes!

Item

| Identification | G1 | Type size | Ident dimension | Max. working pressure (bar) | System |
|---------------------|--------------|-----------|-----------------|-----------------------------|-----------|
| MV IG 10/25 | G 1" -11 | 25 | 35,0 | 50 | 22 / 23,5 |
| MV IG 10-MA | G 1" -11 | - | 37,5 | 50 | May |
| MV IG 10-X25 | G 1" -11 | X25 | 41,0 | 50 | 22 / 23,5 |
| MV IG 10/35 | G 1" -11 | 35 | 49,5 | 50 | 22 |
| MV IG 54-X25 | G 1.1/4" -11 | X25 | 41,0 | 50 | 22 / 23,5 |
| MV IG 54/35 | G 1.1/4" -11 | 35 | 49,5 | 50 | 22 |
| MV IG 54/50 | G 1.1/4" -11 | 50 | 63,0 | 50 | 22 |
| MV IG 15/35 | G 1.1/2" -11 | 35 | 49,5 | 50 | 22 |
| MV IG 15/42 | G 1.1/2" -11 | 42 | 53,0 | 50 | 22 / 23,5 |
| MV IG 15/50 | G 1.1/2" -11 | 50 | 63,0 | 50 | 22 |
| MV IG 20/35 | G 2" -11 | 35 | 49,5 | 50 | 22 |
| MV IG 20/50 | G 2" -11 | 50 | 63,0 | 50 | 22 |
| MV IG 25/50 | G 2.1/2" -11 | 50 | 63,0 | 50 | 22 |
| MV IG 25/65 | G 2.1/2" -11 | 65 | 73,0 | 25 | 22 / 23,5 |