

### Properties

Application	for mortar, concrete, screed supply on pumps, sprayers and plastering machines
Connection 1	BSP cylindrical internal threads
Connection 2	Coupling male connection
Special features	TÜV tested
Media	Mortar, concrete, screed
Material	Steel Malleable cast iron
Surface	electro galvanised



### Note

Type size 25 and MMIG10-MA have one lever, all other type sizes have 2 levers.

Note: Parts must only replaced with parts of the same type sizes!

### Item

Identification	G1	Type size	Ident dimension	Max. working pressure (bar)	System
<b>MV IG 10/25</b>	G 1" -11	25	35,0	50	22 / 23,5
<b>MV IG 10-MA</b>	G 1" -11	-	37,5	50	May
<b>MV IG 10-X25</b>	G 1" -11	X25	41,0	50	22 / 23,5
<b>MV IG 10/35</b>	G 1" -11	35	49,5	50	22
<b>MV IG 54-X25</b>	G 1.1/4" -11	X25	41,0	50	22 / 23,5
<b>MV IG 54/35</b>	G 1.1/4" -11	35	49,5	50	22
<b>MV IG 54/50</b>	G 1.1/4" -11	50	63,0	50	22
<b>MV IG 15/35</b>	G 1.1/2" -11	35	49,5	50	22
<b>MV IG 15/42</b>	G 1.1/2" -11	42	53,0	50	22 / 23,5
<b>MV IG 15/50</b>	G 1.1/2" -11	50	63,0	50	22
<b>MV IG 20/35</b>	G 2" -11	35	49,5	50	22
<b>MV IG 20/50</b>	G 2" -11	50	63,0	50	22
<b>MV IG 25/50</b>	G 2.1/2" -11	50	63,0	50	22
<b>MV IG 25/65</b>	G 2.1/2" -11	65	73,0	25	22 / 23,5