


# PVC ANTI AB PU

## PVC suction and delivery hose

### Properties

<b>Application</b>	Construction industry Agricultural technology
<b>Special features</b>	weatherproof exceptionally abrasion resistant flexible .
<b>Inner layer</b>	Polyurethane
<b>Insert</b>	Hard PVC spiral
<b>Outer layer</b>	Polyurethane
<b>Colour</b>	metallic green
<b>Temp. min.</b>	-25 °C
<b>Temp. max.</b>	55 °C
<b>Media</b>	Cereals Cement Gravel Granulates



### Item

Identification	Inches	Internal Ø (mm)	Wall thickness (mm)	BD* at 20°C (bar)	Vacuum (bar)	Min. bending radius (mm)	Roll length (m)
PVC ANTI AB 63-6 PU	2.1/2"	63	5,5	4,0	0,7	250	30 / 50
PVC ANTI AB 76-6.5 PU	3"	76	6,7	4,0	0,7	300	30 / 50
PVC ANTI AB 102-7 PU	4"	102	8,5	3,0	0,7	400	30 / 50
PVC ANTI AB 127-8 PU	5"	127	9,5	2,5	0,7	510	30
PVC ANTI AB 152-9 PU	6"	152	11,0	2,0	0,7	610	20

BD = Working pressure