


PVC ANTI AB PU

PVC suction and delivery hose

Properties

| | |
|-------------------------|----------------------------------------------------------------|
| Application | Construction industry Agricultural technology |
| Special features | weatherproof exceptionally abrasion resistant flexible . |
| Inner layer | Polyurethane |
| Insert | Hard PVC spiral |
| Outer layer | Polyurethane |
| Colour | metallic green |
| Temp. min. | -25 °C |
| Temp. max. | 55 °C |
| Media | Cereals Cement Gravel Granulates |



Item

| Identification | Inches | Internal Ø (mm) | Wall thickness (mm) | BD* at 20°C (bar) | Vacuum (bar) | Min. bending radius (mm) | Roll length (m) |
|-----------------------|--------|--------------------|------------------------|----------------------|-----------------|-----------------------------|--------------------|
| PVC ANTI AB 63-6 PU | 2.1/2" | 63 | 5,5 | 4,0 | 0,7 | 250 | 30 / 50 |
| PVC ANTI AB 76-6.5 PU | 3" | 76 | 6,7 | 4,0 | 0,7 | 300 | 30 / 50 |
| PVC ANTI AB 102-7 PU | 4" | 102 | 8,5 | 3,0 | 0,7 | 400 | 30 / 50 |
| PVC ANTI AB 127-8 PU | 5" | 127 | 9,5 | 2,5 | 0,7 | 510 | 30 |
| PVC ANTI AB 152-9 PU | 6" | 152 | 11,0 | 2,0 | 0,7 | 610 | 20 |

BD = Working pressure