


# PVC WAS ELAST

PVC water hose

## Properties

<b>Application</b>	Agricultural technology
<b>Special features</b>	durable resistant to pressure and abrasion flexible weatherproof
<b>Standard</b>	ISO 1307
<b>Inner layer</b>	stable, high flexibility, smooth plasticised PVC
<b>Insert</b>	impact and pressure resistant PVC reinforcing spiral
<b>Outer layer</b>	slightly ribbed outer surface
<b>Temp. min.</b>	-20 °C
<b>Temp. max.</b>	50 °C
<b>Media</b>	Water



## Item

Identification	Inches	Internal Ø (mm)	BD* at 20°C (bar)	Burst pressure (bar)	Vacuum (bar)	Min. bending radius (mm)	Roll length (m)
PVC WAS 25 ELAST	1"	25	7,0	20	0,9	90	50
PVC WAS 32 ELAST	1.1/4"	32	6,0	17	0,9	130	50
PVC WAS 38 ELAST	1.1/2"	38	6,0	16	0,9	140	50
PVC WAS 51 ELAST	2"	51	5,0	15	0,9	200	50
PVC WAS 63 ELAST	2.1/2"	63	4,5	14	0,9	275	50
PVC WAS 76 ELAST	3"	76	4,0	12	0,9	310	50
PVC WAS 90 ELAST	3.1/2"	90	3,5	10	0,9	375	50
PVC WAS 102 ELAST	4"	102	3,0	10	0,9	410	20 / 30
PVC WAS 110 ELAST	4.3/8"	110	3,0	10	0,9	450	20 / 30
PVC WAS 127 ELAST	5"	127	2,5	9	0,9	520	20 / 30
PVC WAS 152 ELAST	6"	152	2,0	9	0,9	610	15

BD = Working pressure