# PYRO WAS RT

Fire service folding hose

HANSA-FLEX

## Properties

| | |
|---|---|
| **Application** | Fire brigade |
| **Special features** | aging and ozone resistant EPDM compound<br>highly elastic and ductile, exceptionally good adhesion values<br>produced using special vulcanisation method<br>exceptionally abrasion resistant |
| **Standard** | DIN 14,811<br>BS6391 |
| **Inner layer** | very strong multifilamant polyester fibres, double-twisted thread, round woven |
| **Colour** | red |
| **Media** | Water |



## Item

| Identification | Inches | Internal Ø (mm) | Operating pressure (bar) | Test pressure (bar) | Burst pressure (bar) | Roll length (m) |
|---|---|---|---|---|---|---|
| **PYRO WAS 38 RT** | 1.1/2" | 38 | 16,0 | 25 | 50 | 15 / 20 / 30 |
| **PYRO WAS 52 RT** | 2" | 52 | 16,0 | 25 | 50 | 15 / 20 / 30 |
| **PYRO WAS 63 RT** | 2.1/2" | 63 | 16,0 | 25 | 50 | 15 / 20 / 30 |
| **PYRO WAS 75 RT** | 3" | 75 | 16,0 | 25 | 50 | 15 / 20 / 30 |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*