

# SVB ND SB

Hose connectors

## Properties

<b>Connection 1</b>	Hose connection
<b>Connection 2</b>	Hose connection
<b>Standard</b>	DIN 20038
<b>Media</b>	Compressed air
<b>Material</b>	Steel



## Note

To be integrated with DIN 20039 B hose clamps.

## Description

maximum hole size for greatest possible flow rate  
rotating nozzle contour enables perfect hose seating

## Item

Identification	for hose ID (mm)	Ø ID (mm)	b (mm)	Length (mm)	Ø Safety collar (mm)	Operating pressure
<b>SVB 13 ND SB</b>	13	9,00	13,5	80	25	PN 25
<b>SVB 15 ND SB</b>	15	12,00	17,0	105	30	PN 25
<b>SVB 19 ND SB</b>	19	16,00	21,0	105	34	PN 25
<b>SVB 25 ND SB</b>	25	22,00	26,5	160	42	PN 25
<b>SVB 32 ND SB</b>	32	27,00	33,5	175	50	PN 25
<b>SVB 38 ND SB</b>	38	33,00	40,0	215	56	PN 25
<b>SVB 50 ND SB</b>	50	45,00	51,0	225	78	PN 25
<b>SVB 53 ND SB</b>	53	46,00	54,0	225	78	PN 25
<b>SVB 75 ND SB</b>	75	68,00	76,0	250	110	PN 25

Ø ID = Through hole