SVB ND SB
Hose connectors

Properties

Connection 1	Hose connection
Connection 2	Hose connection
Standard	DIN 20038
Media	Compressed air
Material	Steel



Note

To be integrated with DIN 20039 B hose clamps.

Description

maximum hole size for greatest possible flow rate
rotating nozzle contour enables perfect hose seating

Item

Identification	for hose ID (mm)	Ø ID (mm)	b (mm)	Length (mm)	Ø Safety collar (mm)	Operating pressure
SVB 13 ND SB	13	9,00	13,5	80	25	PN 25
SVB 15 ND SB	15	12,00	17,0	105	30	PN 25
SVB 19 ND SB	19	16,00	21,0	105	34	PN 25
SVB 25 ND SB	25	22,00	26,5	160	42	PN 25
SVB 32 ND SB	32	27,00	33,5	175	50	PN 25
SVB 38 ND SB	38	33,00	40,0	215	56	PN 25
SVB 50 ND SB	50	45,00	51,0	225	78	PN 25
SVB 53 ND SB	53	46,00	54,0	225	78	PN 25
SVB 75 ND SB	75	68,00	76,0	250	110	PN 25

Ø ID = Through hole

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.