# TRD
Threaded nozzle

## Properties

| | |
|---|---|
| **Application** | in construction, mining and tunnel building |
| **Connection 1** | round external thread |
| **Connection 2** | Hose connection |
| **Media** | Compressed air, water |
| **Material** | Steel |
| **Surface** | electro galvanised |



## Note

To be integrated with DIN 20,039 A hose clamps.

## Description

fits conical nozzle threaded connections
rotating nozzle contour enables perfect hose seating

## Item

| Identification | for hose ID (mm) | G1 | Ø ID (mm) | Length (mm) | Nozzle length (mm) | AF (mm) | Cone | Operating pressure |
|---|---|---|---|---|---|---|---|---|
| **TRD 32-13 MM** | 13 | Rd 32 x 1/8" | 10,00 | 75 | 41 | 32 | 1:3 | PN 25 |
| **TRD 32-16 MM** | 16 | Rd 32 x 1/8" | 12,00 | 75 | 41 | 32 | 1:3 | PN 25 |
| **TRD 32-19 MM** | 19 | Rd 32 x 1/8" | 15,00 | 75 | 41 | 32 | 1:3 | PN 25 |
| **TRD 32-25 MM** | 25 | Rd 32 x 1/8" | 20,00 | 75 | 41 | 32 | 1:3 | PN 25 |

AF = Width across flats – Ø ID = Through hole

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*