TUE M SB
Threaded nozzle

Properties

Application	Systems engineering Industry and construction
Connection 1	BSP cylindrical internal threads
Connection 2	Hose connection
Media	Compressed air
Material	Steel
Surface	electro galvanised



Note

To be integrated with DIN 20039 B hose clamps.

Description

rotating nozzle contour enables perfect hose seating
maximum hole size for greatest possible flow rate

Item

Identification	Connecting thread	for hose ID (mm)	Ø ID (mm)	Length (mm)	Thread length (mm)	Nozzle length (mm)	Ø Safety collar (mm)	AF (mm)	Operating pressure
TUE 34 19 M SB	G 3/4" -14	19	15,00	71	19	40	32	32	PN 25
TUE 1 19 M SB	G 1" -11	19	15,00	73	20	40	32	41	PN 25
TUE 1 25 M SB	G 1" -11	25	20,00	75	20	41	36	41	PN 25
TUE 114 25 M SB	G 1.1/4" -11	25	20,00	80	23	41	36	50	PN 25
TUE 114 32 M SB	G 1.1/4" -11	32	25,00	86	23	48	45	50	PN 25

AF = Width across flats – Ø ID = Through hole

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.