

Properties						
Application	Construction industry					
Special features	pricked					
Standard	DIN 53516 < 65 mm3					
Inner layer	highly abrasion resistant insulating NBR/CBR rubber					
Insert	four highly tear-resistant braided steel wires					
Outer layer	synthetic rubber with high ozone, abrasion, and weather resistance					
Colour	black					
Temp. min.	-40 °C					
Temp. max.	70 °C					
Media	Mortar, concrete, screed					



Item							
Identification	Inches	Internal Ø	External Ø	Operating pressure (bar)	Burst pressure	Min. bending radius	Roll length
BETON 85-50-10	2"	50,8	70	85,0	200	508	30,5 / 61,0
BETON 85-65-11	2.1/2"	63,5	88	85,0	200	635	30,5 / 61,0
BETON 85-75-11.5	3"	76,2	102	85,0	200	762	30,5 / 61,0
BETON 85-80-13	3.1/4"	80,0	106	85,0	200	-	30,5 / 61,0
BETON 85-100-14	4"	101,6	130	85,0	200	1016	30,5 / 61,0
BETON 85-127-14	5"	127,0	155	85,0	200	1270	30,5 / 61,0
BETON 85-152-16	6"	152,4	184	85,0	200	1524	30,5 / 61,0