


# GOLDSCHLANGE

Water and cleaning hose

**HANSA FLEX**

## Properties

<b>Application</b>	Agricultural technology Construction industry Systems engineering
<b>Special features</b>	ozone and abrasion resistance weatherproof Wide range of chemical media kink and impact resistant, traversable UV resistant steam up to +130°C (approx. 30 minutes)
<b>Inner layer</b>	black, porous, smooth EPDM lining
<b>Insert</b>	two synthetic thread braided inserts
<b>Outer layer</b>	oil, grease and chemical resistant CR rubber
<b>Colour</b>	black with yellow wavy line
<b>Temp. min.</b>	-30 °C
<b>Temp. max.</b>	100 °C
<b>Media</b>	Water



## Item

Identification	Inches	Internal Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)	Roll length (m)
<b>GOLDSCHLANGE 10</b>	3/8"	10	3,5	30,0	90	45	40
<b>GOLDSCHLANGE 13</b>	1/2"	13	3,9	30,0	90	50	40
<b>GOLDSCHLANGE 16</b>	5/8"	16	3,6	25,0	70	70	40
<b>GOLDSCHLANGE 19</b>	3/4"	19	4,4	25,0	75	80	40
<b>GOLDSCHLANGE 22</b>	7/8"	22	4,5	20,0	60	100	40
<b>GOLDSCHLANGE 25</b>	1"	25	4,5	20,0	60	110	40
<b>GOLDSCHLANGE 32</b>	1.1/4"	32	5,5	12,0	36	175	40
<b>GOLDSCHLANGE 38</b>	1.1/2"	38	6,5	12,0	36	250	40
<b>GOLDSCHLANGE 50</b>	2"	50	7,5	10,0	30	300	40