


GOLDSCHLANGE

Water and cleaning hose

HANSA FLEX

Properties

Application	Agricultural technology Construction industry Systems engineering
Special features	ozone and abrasion resistance weatherproof Wide range of chemical media kink and impact resistant, traversable UV resistant steam up to +130°C (approx. 30 minutes)
Inner layer	black, porous, smooth EPDM lining
Insert	two synthetic thread braided inserts
Outer layer	oil, grease and chemical resistant CR rubber
Colour	black with yellow wavy line
Temp. min.	-30 °C
Temp. max.	100 °C
Media	Water



Item

Identification	Inches	Internal Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)	Roll length (m)
GOLDSCHLANGE 10	3/8"	10	3,5	30,0	90	45	40
GOLDSCHLANGE 13	1/2"	13	3,9	30,0	90	50	40
GOLDSCHLANGE 16	5/8"	16	3,6	25,0	70	70	40
GOLDSCHLANGE 19	3/4"	19	4,4	25,0	75	80	40
GOLDSCHLANGE 22	7/8"	22	4,5	20,0	60	100	40
GOLDSCHLANGE 25	1"	25	4,5	20,0	60	110	40
GOLDSCHLANGE 32	1.1/4"	32	5,5	12,0	36	175	40
GOLDSCHLANGE 38	1.1/2"	38	6,5	12,0	36	250	40
GOLDSCHLANGE 50	2"	50	7,5	10,0	30	300	40