

GOLDSCHLANGE

Water and cleaning hose

HANSA FLEX

Properties

| | |
|-------------------------|--|
| Application | Agricultural technology Construction industry Systems engineering |
| Special features | ozone and abrasion resistance weatherproof Wide range of chemical media kink and impact resistant, traversable UV resistant steam up to +130°C (approx. 30 minutes) |
| Inner layer | black, porous, smooth EPDM lining |
| Insert | two synthetic thread braided inserts |
| Outer layer | oil, grease and chemical resistant CR rubber |
| Colour | black with yellow wavy line |
| Temp. min. | -30 °C |
| Temp. max. | 100 °C |
| Media | Water |



Item

| Identification | Inches | Internal Ø (mm) | Wall thickness (mm) | Operating pressure (bar) | Burst pressure (bar) | Min. bending radius (mm) | Roll length (m) |
|------------------------|--------|--------------------|------------------------|-----------------------------|-------------------------|-----------------------------|--------------------|
| GOLDSCHLANGE 10 | 3/8" | 10 | 3,5 | 30,0 | 90 | 45 | 40 |
| GOLDSCHLANGE 13 | 1/2" | 13 | 3,9 | 30,0 | 90 | 50 | 40 |
| GOLDSCHLANGE 16 | 5/8" | 16 | 3,6 | 25,0 | 70 | 70 | 40 |
| GOLDSCHLANGE 19 | 3/4" | 19 | 4,4 | 25,0 | 75 | 80 | 40 |
| GOLDSCHLANGE 22 | 7/8" | 22 | 4,5 | 20,0 | 60 | 100 | 40 |
| GOLDSCHLANGE 25 | 1" | 25 | 4,5 | 20,0 | 60 | 110 | 40 |
| GOLDSCHLANGE 32 | 1.1/4" | 32 | 5,5 | 12,0 | 36 | 175 | 40 |
| GOLDSCHLANGE 38 | 1.1/2" | 38 | 6,5 | 12,0 | 36 | 250 | 40 |
| GOLDSCHLANGE 50 | 2" | 50 | 7,5 | 10,0 | 30 | 300 | 40 |