


## Properties

<b>Application</b>	Food industry
<b>Special features</b>	highly flexible and traversable totally neutral odour and taste homogeneous, smooth and unplasticised steam up to 130°C
<b>Approval</b>	KTW guideline "Pipes", DVGW-W270 and DVGW-VP 549 (DVGW reg. no.: DW-0309BT0079)
<b>Inner layer</b>	special transparent, plastomer coating
<b>Insert</b>	PES intermediate layer and two cord inserts
<b>Outer layer</b>	NBR resistant to abrasion, UV, greases and oils
<b>Colour</b>	blue with yellow wavy line
<b>Temp. min.</b>	-20 °C
<b>Temp. max.</b>	90 °C
<b>Media</b>	Water



## Item

Identification	Inches	Internal Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)	Roll length (m)
AQUAPAL 10-3.6	3/8"	10	3,6	20,0	60	60	40
AQUAPAL 13-3.6	1/2"	13	3,6	20,0	60	75	40
AQUAPAL 16-3.6	5/8"	16	3,6	20,0	60	95	40
AQUAPAL 19-4.2	3/4"	19	4,2	20,0	60	110	40
AQUAPAL 22-4.5	7/8"	22	4,5	20,0	60	130	40
AQUAPAL 25-4.5	1"	25	4,5	20,0	60	145	40
AQUAPAL 32-4.5	1.1/4"	32	5,5	20,0	60	280	40
AQUAPAL 38-6.5	1.1/2"	38	6,5	20,0	60	330	40
AQUAPAL 50-7.5	2"	50	7,5	20,0	60	435	40