


Properties					
Application	Swage fitting for HD 400 hoses				
Connection 1	metric nut thread				
Sealing form 1	24° outer cone with O-ring				
Short code	DKOL				
Standard	ISO 8434-1				
Integration	with pull-out protection (interlock)				
Scope of supply	Swage nipple + swage ferrule				
Material	Steel				
Surface	electro galvanised				
Series	light				





DN	Size	Inches	G1	for external pipe Ø	L1 (mm)	OR
10	6	3/8"	M 18 x 1.5	12	69,3	9.0 x 1.5
12	8	1/2"	M 22 x 1.5	15	70,8	12.0 x 2.0
16	10	5/8"	M 26 x 1.5	18	88,2	15.0 x 2.0
16	10	5/8"	M 30 x 2	22	86,0	20.0 x 2.0
	10 12 16	10 6 12 8 16 10	10 6 3/8" 12 8 1/2" 16 10 5/8"	10 6 3/8" M 18 x 1.5 12 8 1/2" M 22 x 1.5 16 10 5/8" M 26 x 1.5	10 6 3/8" M 18 x 1.5 12 12 8 1/2" M 22 x 1.5 15 16 10 5/8" M 26 x 1.5 18	(mm) (mm) 10 6 3/8" M 18 x 1.5 12 69,3 12 8 1/2" M 22 x 1.5 15 70,8 16 10 5/8" M 26 x 1.5 18 88,2