

# PA 700 AOS 45

Swage fitting, DKOS angle 45°

**HANSA FLEX**

## Properties

<b>Application</b>	Swage fitting for HD 400 hoses
<b>Connection 1</b>	metric nut thread
<b>Sealing form 1</b>	24° outer cone with O-ring
<b>Short code</b>	DKOS
<b>Standard</b>	ISO 8434-1
<b>Integration</b>	with pull-out protection (interlock)
<b>Scope of supply</b>	Swage nipple + swage ferrule
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised
<b>Series</b>	heavy



Item											
Identification	DN	Size	Inches	Operating pressure (bar)	G1	for external pipe Ø (mm)	L1 (mm)	S1	L2 (mm)	OR	
PA 710 AOS 08 45	10	6	3/8"	630,0	M 20 x 1.5	12	-	24	-	10.0 x 1.5	
PA 710 AOS 45	10	6	3/8"	630,0	M 22 x 1.5	14	94,2	27	-	12.0 x 2.0	
PA 713 AOS 45	12	8	1/2"	420,0	M 24 x 1.5	16	95,0	30	21,5	13.0 x 2.0	
PA 713 AOS 16 45	12	8	1/2"	420,0	M 30 x 2	20	108,0	36	27,0	17.5 x 2.5	
PA 716 AOS 45	16	10	3/8"	420,0	M 30 x 2	20	118,0	36	27,0	17.5 x 2.5	
PA 720 AOS 16 45	19	12	3/4"	420,0	M 30 x 2	20	133,0	36	27,0	16.0 x 2.5	
PA 720 AOS 45	19	12	3/4"	420,0	M 36 x 2	25	136,0	46	30,0	20.0 x 2.5	
PA 720 AOS 25 45	19	12	3/4"	420,0	M 42 x 2	30	142,0	50	35,0	27.0 x 2.5	
PA 725 AOS 20 45	25	16	1"	420,0	M 36 x 2	25	156,5	41	34,5	20.0 x 2.5	
PA 725 AOS 45	25	16	1"	420,0	M 42 x 2	30	164,0	50	34,5	25.0 x 2.5	
PA 725 AOS 32 45	25	16	1"	420,0	M 52 x 2	38	170,0	60	41,0	33.0 x 2.5	