PA 700 SF6 90


Swage fitting, SFS angle 90°

HANSA-FLEX

Properties

Application	Swage fitting for HD 400 hoses
Connection 1	SAE flange connection 6000 PSI
Sealing form 1	flat seal with SF O-ring
Short code	SFS
Standard	SAE J518 ISO 6162-2
Integration	with pull-out protection (interlock)
Scope of supply	Swage nipple + swage ferrule
Material	Steel
Surface	electro galvanised





Item

Identification	DN	Size	Inches	Flange size	Operating pressure (bar)	D (mm)	H (mm)	L1 (mm)	L2 (mm)
PA 713 SF6 90	12	8	1/2"	1/2"	420,0	31,8	7,7	86,0	46,0
PA 713 SF6 20 90	12	8	1/2"	3/4"	420,0	41,3	8,8	92,5	46,0
PA 716 SF6 13 90	16	10	5/8"	1/2"	420,0	31,8	7,7	108,0	48,0
PA 716 SF6 20 90	16	10	5/8"	3/4"	420,0	41,3	8,8	107,5	52,5
PA 716 SF6 25 90	16	10	5/8"	1"	420,0	47,6	9,5	108,0	57,0
PA 720 SF6 90	19	12	3/4"	3/4"	420,0	41,3	8,8	127,5	62,0
PA 720 SF6 25 90	19	12	3/4"	1"	420,0	47,6	9,6	127,5	68,0
PA 725 SF6 20 90	25	16	1"	3/4"	420,0	41,3	8,8	152,5	70,5
PA 725 SF6 90	25	16	1"	1"	420,0	47,6	9,6	158,0	74,0
PA 725 SF6 32 90	25	16	1"	1.1/4"	420,0	54,0	10,4	156,0	83,5

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.