

Properties

| | |
|-------------------------|---|
| Application | for unloading cement, sand, gravel and granulates from silo transport vehicles. |
| Special features | abrasion value according to DIN 53516 < 65 mm ³ |
| Standard | ISO 1307 |
| Inner layer | highly abrasion resistant insulating natural rubber |
| Insert | highly tear-resistant synthetic textile insert and copper braid |
| Outer layer | special synthetic rubber, highly resistant to abrasion, ozone and weather, pricked. |
| Colour | black |
| Temp. min. | -40 °C |
| Temp. max. | 70 °C |
| Media | Cement Sand Gravel Granulates |



Item

| Identification | Inches | Internal Ø (mm) | External Ø (mm) | Operating pressure (bar) | Burst pressure (bar) | Min. bending radius (mm) | Roll length (m) |
|---------------------|--------|--------------------|--------------------|-----------------------------|-------------------------|-----------------------------|--------------------|
| SILO 25-6 | 1" | 25,4 | 37,0 | 10,0 | 30 | 254 | 40 |
| SILO 32-6 | 1.1/4" | 32,0 | 44,0 | 10,0 | 30 | 320 | 40 |
| SILO 38-6 | 1.1/2" | 38,0 | 50,0 | 10,0 | 30 | 380 | 40 |
| SILO 51-6.5 | 2" | 50,8 | 64,5 | 10,0 | 30 | 508 | 40 |
| SILO 63-7 | 2.1/2" | 63,5 | 77,0 | 10,0 | 30 | 635 | 40 |
| SILO 76-7 | 3" | 76,2 | 90,0 | 10,0 | 30 | 762 | 40 |
| SILO 90-7 | 3.1/2" | 90,0 | 104,0 | 10,0 | 30 | 900 | 40 |
| SILO 102-8 | 4" | 101,6 | 118,0 | 10,0 | 30 | 1016 | 40 |
| SILO 127-9.5 | 5" | 127,0 | 146,0 | 10,0 | 30 | 1270 | 40 |
| SILO 152-10 | 6" | 152,4 | 172,0 | 10,0 | 30 | 1524 | 40 |
| SILO 203-11 | 8" | 203,2 | 225,0 | 10,0 | 30 | 2032 | 20 |
| SILO 254-11 | 10" | 254,0 | 276,0 | 10,0 | 30 | 2540 | 20 |