

# SANDSTRAHL

Sandblasting hose

**HANSA FLEX**

## Properties

<b>Application</b>	for cleaning metal, stone and other surfaces and supplying highly abrasive media
<b>Inner layer</b>	highly abrasion resistant insulating natural rubber
<b>Insert</b>	highly tear-resistant synthetic textile insert and copper braid
<b>Outer layer</b>	Natural and synthetic rubber, abrasion, ozone and weather resistant pricked
<b>Colour</b>	black
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	70 °C
<b>Media</b>	Sand



## Item

Identification	Internal Ø (mm)	External Ø (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)	Roll length (m)
SANDSTRAHL 13-7	13	27	12,0	36	127	40
SANDSTRAHL 19-7	19	33	12,0	36	190	40
SANDSTRAHL 25-7	25	39	12,0	36	254	40
SANDSTRAHL 32-8	32	48	12,0	36	320	40
SANDSTRAHL 38-9	38	56	12,0	36	380	40
SANDSTRAHL 51-11	51	69	12,0	36	510	40
SANDSTRAHL 63-9.5	63	82	12,0	36	635	40