


# PVC KANAL

PVC-BUNA ditch suction hose, grey

## Properties

<b>Special features</b>	especially for use in very cold climates
<b>Standard</b>	ISO 1307
<b>Inner layer</b>	stable, high flexibility, smooth plasticised PVC
<b>Insert</b>	impact and pressure resistant PVC reinforcing spiral
<b>Outer layer</b>	stable, high flexibility, smooth plasticised PVC
<b>Colour</b>	grey
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	50 °C



## Item

Identification	Inches	Internal Ø (mm)	Wall thickness (mm)	Burst pressure (bar)	Vacuum (bar)	Min. bending radius (mm)
PVC KANAL DN 25	1"	25	4,2	18	0,9	115
PVC KANAL DN 32	1.1/4"	32	4,2	15	0,9	125
PVC KANAL DN 38	1.1/2"	38	4,5	14	0,9	145
PVC KANAL DN 40	-	40	4,5	13	0,9	160
PVC KANAL DN 51	2"	51	5,0	13	0,9	180
PVC KANAL DN 60	-	60	5,0	13	0,9	200
PVC KANAL DN 63	2.1/2"	63	5,5	12	0,9	220
PVC KANAL DN 76	3"	76	5,5	10	0,9	250
PVC KANAL DN 80	-	80	6,0	10	0,9	260
PVC KANAL DN 90	-	90	6,0	9	0,8	305
PVC KANAL DN 102	4"	102	6,5	9	0,8	335