

# SSKK IR

## Sandblasting coupling IR

### Properties

|                     |  |
|---------------------|--|
| <b>Application</b>  | for sandblasting systems and cabs (fixed / mobile) |
| <b>Connection 1</b> | BSP cylindrical internal threads                   |
| <b>Connection 2</b> | Claw coupling                                      |
| <b>Material</b>     | Malleable cast iron                                |
| <b>Surface</b>      | electro galvanised                                 |



### Item

| Identification         | G1           | b<br>(mm) | h<br>(mm) | Cog space<br>(mm) | Max. working pressure<br>(bar) |
|------------------------|--------------|-----------|-----------|-------------------|--------------------------------|
| <b>SSKK NW 32 IR</b>   | G 1.1/4" -11 | 87        | 55        | 58                | 12                             |
| <b>SSKK NW 32 IR-N</b> | G 1.1/4" -11 | 87        | 62        | 58                | 12                             |
| <b>SSKK NW 38 IR</b>   | G 1.1/2" -11 | 87        | 55        | 58                | 12                             |
| <b>SSKK NW 38 IR-N</b> | G 1.1/2" -11 | 87        | 62        | 58                | 12                             |
| <b>SSKK NW 50 IR</b>   | G 2" -11     | 87        | 84        | 58                | 12                             |