

# PRT M DN

Perrot coupling female part, with hose connection

**HANSA FLEX**

## Properties

**Connection 1** Coupling female connection

**Sealing form 1** O-ring sealed

**Connection 2** Hose connection

**Material** Steel

**Surface** hot galvanised



Item			
Identification	Operating pressure (bar)	Coupling dimension (mm)	for hose ID (mm)
PRT M 50 DN 50	12,0	50,0	50
PRT M 70 DN 63	12,0	70,0	63
PRT M 70 DN 70	12,0	70,0	70
PRT M 70 DN 75	12,0	70,0	75
PRT M 89 DN 75	12,0	89,0	75
PRT M 89 DN 80	12,0	89,0	80
PRT M 89 DN 89	12,0	89,0	89
PRT M 108 DN 75	12,0	108,0	75
PRT M 108 DN 90	12,0	108,0	90
PRT M 108 DN 102	12,0	108,0	102
PRT M 108 DN 110	12,0	108,0	110
PRT M 108 DN 127	12,0	108,0	127
PRT M 108 DN 152	12,0	108,0	152
PRT M 133 DN 50	12,0	133,0	50
PRT M 133 DN 76	12,0	133,0	76
PRT M 133 DN 102	12,0	133,0	102
PRT M 133 DN 110	12,0	133,0	110
PRT M 133 DN 127	12,0	133,0	127
PRT M 133 DN 133	12,0	133,0	133
PRT M 133 DN 152	12,0	133,0	152
PRT M 159 DN 50	12,0	159,0	50
PRT M 159 DN 76	12,0	159,0	76
PRT M 159 DN 102	12,0	159,0	102
PRT M 159 DN 127	12,0	159,0	127
PRT M 159 DN 133	12,0	159,0	133
PRT M 159 DN 152	12,0	159,0	152
PRT M 159 DN 159	12,0	159,0	159
PRT M 216 DN 200	12,0	216,0	200