PRT M DN

Perrot coupling female part, with hose connection

HANSA-FLEX

Properties

Connection 1	Coupling female connection
Sealing form 1	O-ring sealed
Connection 2	Hose connection
Material	Steel
Surface	hot galvanised



Item

Identification	Operating pressure (bar)	Coupling dimension (mm)	for hose ID (mm)
PRT M 50 DN 50	12,0	50,0	50
PRT M 70 DN 63	12,0	70,0	63
PRT M 70 DN 70	12,0	70,0	70
PRT M 70 DN 75	12,0	70,0	75
PRT M 89 DN 75	12,0	89,0	75
PRT M 89 DN 80	12,0	89,0	80
PRT M 89 DN 89	12,0	89,0	89
PRT M 108 DN 75	12,0	108,0	75
PRT M 108 DN 90	12,0	108,0	90
PRT M 108 DN 102	12,0	108,0	102
PRT M 108 DN 110	12,0	108,0	110
PRT M 108 DN 127	12,0	108,0	127
PRT M 108 DN 152	12,0	108,0	152
PRT M 133 DN 50	12,0	133,0	50
PRT M 133 DN 76	12,0	133,0	76
PRT M 133 DN 102	12,0	133,0	102
PRT M 133 DN 110	12,0	133,0	110
PRT M 133 DN 127	12,0	133,0	127
PRT M 133 DN 133	12,0	133,0	133
PRT M 133 DN 152	12,0	133,0	152
PRT M 159 DN 50	12,0	159,0	50
PRT M 159 DN 76	12,0	159,0	76
PRT M 159 DN 102	12,0	159,0	102
PRT M 159 DN 127	12,0	159,0	127
PRT M 159 DN 133	12,0	159,0	133
PRT M 159 DN 152	12,0	159,0	152
PRT M 159 DN 159	12,0	159,0	159
PRT M 216 DN 200	12,0	216,0	200

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.