

PRT S DN

Perrot coupling male part, with hose connection

Properties

Connection 1 Coupling male connection

Material Steel

Surface black



| Item | | | |
|------------------|-----------------------------|----------------------------|---------------------|
| Identification | Operating pressure (bar) | Coupling dimension (mm) | for hose ID (mm) |
| PRT S 50 DN 50 | 12,0 | 50,0 | 50 |
| PRT S 70 DN 63 | 12,0 | 70,0 | 63 |
| PRT S 70 DN 70 | 12,0 | 70,0 | 70 |
| PRT S 70 DN 75 | 12,0 | 70,0 | 75 |
| PRT S 89 DN 75 | 12,0 | 89,0 | 75 |
| PRT S 89 DN 80 | 12,0 | 89,0 | 80 |
| PRT S 89 DN 89 | 12,0 | 89,0 | 89 |
| PRT S 108 DN 75 | 12,0 | 108,0 | 75 |
| PRT S 108 DN 90 | 12,0 | 108,0 | 90 |
| PRT S 108 DN 102 | 12,0 | 108,0 | 102 |
| PRT S 108 DN 110 | 12,0 | 108,0 | 110 |
| PRT S 108 DN 152 | 12,0 | 108,0 | 152 |
| PRT S 108 DN 127 | 12,0 | 108,0 | 127 |
| PRT S 133 DN 50 | 12,0 | 133,0 | 50 |
| PRT S 133 DN 76 | 12,0 | 133,0 | 76 |
| PRT S 133 DN 102 | 12,0 | 133,0 | 102 |
| PRT S 133 DN 110 | 12,0 | 133,0 | 110 |
| PRT S 133 DN 127 | 12,0 | 133,0 | 127 |
| PRT S 133 DN 133 | 12,0 | 133,0 | 133 |
| PRT S 133 DN 152 | 12,0 | 133,0 | 152 |
| PRT S 159 DN 50 | 12,0 | 159,0 | 50 |
| PRT S 159 DN 76 | 12,0 | 159,0 | 76 |
| PRT S 159 DN 102 | 12,0 | 159,0 | 102 |
| PRT S 159 DN 127 | 12,0 | 159,0 | 127 |
| PRT S 159 DN 133 | 12,0 | 159,0 | 133 |
| PRT S 159 DN 152 | 12,0 | 159,0 | 152 |
| PRT S 159 DN 159 | 12,0 | 159,0 | 159 |
| PRT S 216 DN 200 | 12,0 | 216,0 | 200 |