

# SKM HL 2 MULTI R

Square multi-coupling (fixed)

## Properties

<b>Application</b>	Industry Transport and municipal vehicles Agricultural technology
<b>Connection 1</b>	metric cylindrical outer thread
<b>Sealing form 1</b>	24° inner cone
<b>Connection 2</b>	Plug in sleeve
<b>Standard</b>	complies with ISO 16028
<b>Residual pressure:</b>	for coupling under residual pressure up to 40 bar on the plug side
<b>Design</b>	Multicoupling
<b>Construction type</b>	Panel construction as quick-change system
<b>max: Flow</b>	100 L/min



## Description

Quick release couplings are used when add-on parts need to be replaced frequently.

## Additional information

Multi couplings offer considerable benefits over bundled screw and plug-in couplings:

- Time saving factor due to fast and convenient exchange of add-on parts
- Convenient handling with simultaneous coupling of multiple connections
- Trouble-free coupling even if system pressures are applied
- No confusion between connections, no reversal of flow paths
- Flat seal valves prevent oil leakages, air admittance and allows efficient cleaning even in soiled working environments

## Item

Identification	for external pipe Ø (mm)	Series	Operating pressure (bar)	Size
SKM 08 HL 2 MULTIR	10	L	200,0	2
SKM 10 HL 2 MULTIR	12	L	200,0	2
SKM 13 HL 2 MULTIR	15	L	200,0	2
SKM 16 HL 2 MULTIR	18	L	200,0	2