SKM HL 2 MULTI R

Square multi-coupling (fixed)

Properties

Application	Industry Transport and municipal vehicles Agricultural technology
Connection 1	metric cylindrical outer thread
Sealing form 1	24° inner cone
Connection 2	Plug in sleeve
Standard	complies with ISO 16028
Residual pressure:	for coupling under residual pressure up to 40 bar on the plug side
Design	Multicoupling
Construction type	Panel construction as quick-change system
max: Flow	100 L/min



Description

Quick release couplings are used when add-on parts need to be replaced frequently.

Additional information

Multi couplings offer considerable benefits
over bundled screw and plug-in couplings:
- Time saving factor due to fast and convenient exchange of add-on parts
- Convenient handling with simultaneous coupling of multiple connections
- Trouble-free coupling even if system pressures are applied
- No confusion between connections, no reversal of flow paths
- Flat seal valves prevent oil leakages, air admittance and
allows efficient cleaning even in soiled working environments

Item

Identification	for external pipe Ø (mm)	Series	Operating pressure (bar)	Size
SKM 08 HL 2 MULTIR	10	L	200,0	2
SKM 10 HL 2 MULTIR	12	L	200,0	2
SKM 13 HL 2 MULTIR	15	L	200,0	2
SKM 16 HL 2 MULTIR	18	L	200,0	2

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.