SKS IR 2 MULTI R

Multicoupling loose half, rectangular



Properties			
Application	Industry Transport and municipal vehicles Agricultural technology		
Connection 1	BSP cylindrical internal threads		
Connection 2	Connectors		
Standard	complies with ISO 16028		
Residual pressure:	for coupling under residual pressure up to 40 bar on the plug side		
Design	Multicoupling		
Construction type	Panel construction as quick-change system		
max: Flow	100 L/min		



Note

Working pressure: 200 bar for each coupling, but no more than 600 bar for the multicoupler

Description

Quick release couplings are used when add-on parts need to be replaced frequently.

Additional information

Multi couplings offer considerable benefits over bundled screw and plug-in couplings:

- Time saving factor due to fast and convenient exchange of add-on parts
- Convenient handling with simultaneous coupling of multiple connections
- Trouble-free coupling even if system pressures are applied
- No confusion between connections, no reversal of flow paths
- Flat seal valves prevent oil leakages, air admittance and allows efficient cleaning even in soiled working environments

Item				
Identification	Connecting thread	Operating pressure	Size	
SKS 10 IR 2 MULTI R	G 3/8" -19	200,0	2	
SKS 13 IR 2 MULTI R	G 1/2" -14	200,0	2	